

STRAPPING UMREIFUNGSBÄNDER



LINDER

Since 1951

LINDER GmbH
Hanomagstr. 22
21244 Buchholz i.d.N.

Delivery adress: Fendtstr. 1
21244 Buchholz i.d.N.
Deutschland/Germany

Fon: + 49 (0) 4181 - 92 88 - 400
info@linder-strapping.com
www.linder-strapping.com

DATA SHEET DATENBLATT

DESCRIPTION BESCHREIBUNG

LINDER PP strapping
LINDER PP Umreifungsband

CHART GRAFIK



TECHNICAL SPECIFICATION TECHNISCHE DATEN

Article number Artikelnummer	11557PP1250SPS
Strap width Bandbreite	12,0 mm ± 5%
Strap thickness Bandstärke	0,50 mm ± 5%
Colour Farbe	black schwarz
Core ID/width Kern/Breite (mm)	~ mm
Outer diameter Außendurchmesser (mm)	~ 0 mm
Curving Säbel (mm/2m)	120/2000 mm/2m
Meters/coil Meter/Spule	~ 1000 m
Surface Oberfläche	gewaffelt
Maximum breaking strength Maximalreißfestigkeit (kg)	128 kg/daN
Nominal elongation Nominaldehnung (%)	12-25 %
Coil weight Rollengewicht (%)	~ 4 kg
Make up Aufmachung	90 coils/pallet Rollen/Palette 1 coils/box Rollen/Karton
Quality standards Qualitätsstandards	DIN EN ISO 9001
Date of issue Datum der Ausstellung	23.10.2024

ohne Kern, mit Kundenlabel

The right of amendments without announcement is reserved. Any responsibility, esp. for special application or patent violation cannot be derived. Only strapping with the term "UV" are particularly protected against the influence of ultraviolet radiation. For questions concerning Product liability the general terms and conditions of the Linder GmbH apply.

Das Recht auf Änderung ohne Ankündigung ist vorbehalten. Eine Haftung welcher Art auch immer, insbesondere für einen bestimmten Einsatzzweck, oder für Patentverletzungen kann daraus nicht abgeleitet werden. Nur Bänder mit der Bezeichnung „UV“ sind besonders gegen den Einfluss von ultravioletter Strahlung geschützt! Bei Produkthaftpflichtfragen gelten die Allgemeinen Geschäftsbedingungen der Linder GmbH.

STRAPPING UMREIFUNGSBÄNDER



LINDER

Since 1951

LINDER GmbH
Hanomagstr. 22
21244 Buchholz i.d.N.

Delivery adress: Fendtstr. 1
21244 Buchholz i.d.N.
Deutschland/Germany

Fon: + 49 (0) 4181 - 92 88 - 400
info@linder-strapping.com
www.linder-strapping.com

DATA SHEET DATENBLATT

DESCRIPTION BESCHREIBUNG

LINDER PP strapping

LINDER PP Umreifungsband

TECHNICAL SPECIFICATION TECHNISCHE DATEN

WITHOUT core, with customer label

The right of amendments without announcement is reserved. Any responsibility, esp. for special application or patent violation cannot be derived. Only strapping with the term "UV" are particularly protected against the influence of ultraviolet radiation. For questions concerning Product liability the general terms and conditions of the Linder GmbH apply.

Das Recht auf Änderung ohne Ankündigung ist vorbehalten. Eine Haftung welcher Art auch immer, insbesondere für einen bestimmten Einsatzzweck, oder für Patentverletzungen kann daraus nicht abgeleitet werden. Nur Bänder mit der Bezeichnung „UV“ sind besonders gegen den Einfluss von ultravioletter Strahlung geschützt! Bei Produkthaftpflichtfragen gelten die Allgemeinen Geschäftsbedingungen der Linder GmbH.